




## G4 Smart e-Blackboard Specifications

<b>Size</b>	<b>86"</b>	
<b>Model</b>	<b>DC860NH</b>	
<b>Manufacturer</b>	<b>ODIN</b>	
<b>Picture</b>		
<b>Size/Structure</b>	<b>Dimensions</b>	<b>Width x Height x Depth</b>
	Combined	4000mm x 1238mm x 93mm
	Middle Part	2000mm x 1238mm x 93mm
	Left Side	1000mm x 1200mm x 93mm
	Left Side (optional)	2000mm x 1200mm x 93mm
	Right Side	1000mm x 1200mm x 93mm
	Right Side (optional)	2000mm x 1200mm x 93mm
<b>Mount</b>	Wall mount or movable stand	
<b>Assembly method</b>	Middle part and two side parts	
<b>Panel</b>	Brightness	500cd/m <sup>2</sup>
	Resolution	3840*2160
	Display ratio	16:9
	Contrast ratio	4000:1
	Color temperature	10000K
	Response time	8 ms
	Refresh Rate	60 Hz @ 4K
	Viewing	178°/178° (Horizontal/Vertical)
	Display size/mm	1895*1066
Life	≥50000h	
<b>Mainboard input/output ports</b>	VGA input*1, HDMI 2.0 input*2, HDMI output*1, RJ45*1, RS232*1, USB Touch*1(Type-B), USB 2.0*1(for Android), USB 3.0*1(for both PC and Android), PC audio in*1, Earphone/Line out*1, OPS PC slot*1	
<b>Front input/output ports</b>	HDMI 2.0 input*1, Type-C*1(Multimedia, support 10W charging), USB 2.0*1(for both PC and Android), USB 3.0*1(for both PC and Android)	

<b>Front buttons</b>	Power: Short press to Power ON display, Turn OFF/ON display backlight; Long press to Power OFF display and put to standby	
	Home: back to Android homepage	
	Setting: to show OSD menu	
	Lock Screen: lock the screen	
	Lock Touch: to lock the touch function	
	Recording: Screen recording	
	Volume +: increase volume	
	Volume -: decrease volume	
<b>Power</b>	Input	100~240V/5A/60HZ/50HZ
	Power	500W(MAX)
	Standby power	0.5w
<b>Speaker</b>	Power: 2*15W	
<b>Wireless microphone (Optional)</b>	Frequency response 30Hz-18KHz, operating time 5h, charging time 2h 5V 800mA, maximum range 10m, transmitter with adjustable sensitivity, receiver with 3.5mm jack, USB charging cable.	
<b>Glass surface</b>	The surface is 4mm Mohs 7 scale hardness heat tempered glass , anti-glare, anti-smash, anti-scratch, anti-reflection and water proof.	
	Suitable for writing with chalk, liquid chalk, glass board markers.	
	Suitable for cleaning with dry or wet sponge or cloth.	
	Full bonding with the panel, gap between LCD panel and the glass is less than 1mm.	
<b>Sides of the board specifics</b>	4mm Mohs 7 scale hardness heat tempered glass, anti-glare, anti-smash, anti-scratch, magnetic, suitable to attach magnets (Visualizer slot with charging).	
<b>Android</b>	Android 8.0, 4G DDR4, 2400MHz, 32GB Flash, with whiteboard function. It supports to play files and open browsers.	
<b>Ethernet</b>	Wired network	Single internet cable supports 1000M width, supports Android and Windows OS online at the same time, supports Android Ethernet up to 1000M width, supports internet online waking up with low power consumption.
	Wireless network	Support 2.4G, 5G dual frequency WiFi, Android and OPS can be online at the same time wirelessly, can realize WiFi Hotspot function. Supports IEEE 802.11a/b/g/n/ac. Supports Bluetooth connection.
<b>Touch</b>	Touch technology	Capacitive touch
	Touch points	20 points
	Touch response	< 4ms
	Writing accuracy	≤ 2mm
	Touch accuracy	< 1mm
	Glass depth	4mm photoelectric glass
	Writing	Fingers, capacitive pen (2 pcs supplied), palm
	OS	Win 7/Win8/Win10

<b>OPS (optional)</b>	CPU	Intel i3/i5/i7
	Memory	4G/8G/16G DDR4
	Hard disk	128G/256G/512G SSD
	OS	Windows 10 Pro
<b>Camera (Optional)</b>	Optional Pixels	8 million :3824(H)*2228(V), 5 million:2592(H)*1944(V);
	Angle	Opposite Angle 120°, Horizontal 98°, Vertical 75°;
	Output picture format	MJPEG/YUV2(YUYV)
	Highest Frame Rate	30fps@24Mhz
	Resolution	10bit ADC
<b>Visualizer (Optional)</b>	Pixels	5 million
	Resolution	up to 2592 * 1944 pixels, autofocus
	Shooting format	≤A4
	Frame Rate	25fps@1080/720p
	Picture output	BMP, JPG, PNG, GIF, TIF
	Video output	FLV, MP4
	Light source	Natural light + LED fill (white)
	Buttons	Power ON/OFF, Photo, Light ON/OFF
	Connection	WiFi 2.4 GHz single frequency supports 802.11b/g/n protocols up to 30m
	Battery	6 hours operation (at maximum power)
<b>N.W</b>	72KG (middle part) 30KG (two sides)	

Add: Odin's Software Park, No. 12-9, Fengji Road, Yuhua Economic Development  
Zone, Nanjing, Jiangsu, China  
Tel: +86 25 5880 6616 Fax:+86 25 5880 6616-8016

Jiangsu Odin Electronic and Technology Co., Ltd